

# MAXXON NEW PRODUCT NAME REFERENCE

PREVIOUS PRODUCT NAME	TO	NEW PRODUCT NAME	PSI
		<b>MAXXON® GYP-CRETE®</b>	
Gyp-Crete®	→	Maxxon Gyp-Crete® Basic	up to 2,200
Gyp-Crete® 2000/3.2K	→	Maxxon Gyp-Crete® 2000/Multifamily	Typical range: 2,000-3,200
Dura-Cap	→	Maxxon Gyp-Crete® High Performance	Typical range: 3,000-4,000
Therma-Floor	→	Maxxon Gyp-Crete® Radiant	Typical range: 2,000-3,200
		<b>MAXXON® COMMERCIAL PRO</b>	
Commercial Topping	→	Maxxon Commercial Pro Level Crete™	Typical range: 4,000-5,000
Level-Right	→	Maxxon Commercial Pro Level-Right®	Typical range: 5,000-7,000
		<b>MAXXON® COMMERCIAL</b>	
Level EZ	→	Maxxon Commercial Level EZ™	Minimum 5,000
Gyp-Crete EZ	→	Maxxon Commercial EZ Crete™	Minimum 3,500
LDF or Level-Right LDF	→	Maxxon Commercial Low Density Fill	28-32 PCF
NA		Maxxon Commercial Gyp-Fix EZ® Patch	Minimum 4,000



# MAXXON PRODUCT LINE – UNDERLAYMENTS PACKAGING

## MAXXON® GYP-CRETE®



## MAXXON® COMMERCIAL PRO



## MAXXON® COMMERCIAL



**MAXXON®**

Bag packaging is not shown at actual size or representation of size according to package weight.